

科目：451 工程力學


系組：土木系

(本試題共 2 頁，第 / 頁)

考生注意：1. 依次序作答，只要標明題號，不必抄題。
 2. 答案必須寫在答案卷上，否則不予計分。
 3. 試題隨卷繳回。

- (1) A steel Z-bar is used as a cantilever beam having a length of 2.0 m . When viewed from the free end toward the fixed end of the beam, the cross section has the orientation and dimensions shown in Figure 1. A concentrated load $P = 14.0\text{ kN}$ acts at the free end of the beam at an angle $\phi = 1.25\text{ rad}$.
- (a) Determine the maximum flexure stress in the beam.
- (b) Determine the deflection of the beam ($E = 200\text{ GPa}$). (30%)

Figure 1



- (2) The state of stress at a point is given by $\sigma_{xx} = -120\text{ MPa}$, $\sigma_{yy} = 140\text{ MPa}$,

$$\sigma_{zz} = 66\text{ MPa}, \sigma_{xy} = 45\text{ MPa}, \sigma_{yz} = -65\text{ MPa}, \text{ and } \sigma_{zx} = 25\text{ MPa}.$$

Determine the three principal stresses and directions associated with the three principal stresses. (25%)

科目：451 工程力學


系組：土木系

(本試題共 2 頁，第 2 頁)

考生注意：1. 依次序作答，只要標明題號，不必抄題。
 2. 答案必須寫在答案卷上，否則不予計分。
 3. 試題隨卷繳回。

- (3) The pin-connected truss in Figure 3 is made of an aluminum alloy for which $E = 72.0 \text{ GPa}$. The magnitudes of the loads are $P = 10 \text{ kN}$ and $Q = 5 \text{ kN}$. Members BC , CD , and DE each have cross-sectional area of 900 mm^2 . The remaining members each have cross-sectional area of 150 mm^2 . Use the energy method to determine the rotation of member BE caused by the loads P and Q . (25%)

Figure 3



- (4) (a) Describe the definition of shear center. (10%)
 (b) For a material subjected to multiaxial states of stress, give one example of failure criteria. (10%)